

High Energy Battery Operated Portable Igniter - Model XE18PBo6



Fitted with internal 12 V 7.2 Ah rechargeable battery and built-in automatic charger



TESI's portable ignition unit is designed to ignite burners without an individual pilot torch or electrode assembly.

The high energy portable unit is also ideal in an emergency situation. For instance, if the main burner's ignition unit fails, the Tesi unit can ignite the burner without needing to be linked to the main power supply.

The unit delivers an output energy of 18 Joules/s Suitable to ignite heavy oils and is not affected by dust, crust, or humidity.

TECHNICAL DATA

POWER SUPPLY UNIT

INPUT VOLTAGE:	12 Vdc
OUTPUT VOLTAGE:	1400 Vdc
OUTPUT ENERGY (per Spark):	18 J
SPARK RATE:	4 Sparks/second
INPUT POWER:	80 W

BATTERY CHARGER

INPUT VOLTAGE:	115 or 230 Vac @ 50 Hz
RECHARGE OUTPUT VOLTAGE:	13.5 Vdc

ENCLOSURE

PROTECTION CLASS:	IP65
MATERIAL:	Aluminium Alloy
DIMENSIONS:	344x272x110
WEIGHT:	5,7 Kg

DATA SUBJECT TO CHANGE WITHOUT NOTICE



IGNITER

Stainless steel construction
 Operating temperature 760°C (1000°C Max)
 Weight: 0.8 Kg for each meter of length
 Length customizable based on customer specification
 HE tip is easily replaceable
 Diameter 17 mm (12/14 mm upon request)
 Rubber handle 150 mm (std) or optional 90° handle.
 Optional adjustable stopping flange.



CONNECTION CABLE

Flexible stainless armoured cable
 External PVC insulation
 ½" NPT straight fittings
 Operating temperature of -20°C to +50°C
 Weight: 0.4 Kg for each meter of length
 Length customizable based on customer specification

XE18PBo6en Rev.01



TESI srl

Sede Operativa: Via Piave 20/11 - 20080 Vermezzo (Milano) Italy
 Tel. +39 02 944 05 01 - Fax +39 02 944 90 87
 e-mail: info@tesigroup.com - www.tesigroup.com

